



FOAM BUMPER PADS for HOTEL CARTS INSTALLATION INSTRUCTIONS

BOING 4000 - Instant Adhesive (Super Glue)

Do not use *Silicone* or other adhesives - as they will not bond adequately



Tools/Equipment: Duct Tape + Cleaning Rag + Sandpaper + Sharp Knife + Solvent

Warning: Do not glue your fingers together with the adhesive!!





Installation Slim "C" Corner Strips

Preparation

1. Lightly sand the existing hard rubber bumper to improve adhesion (remove any old or peeling paint)
2. Thoroughly clean the hard rubber bumper and metal frame with Solvent to remove all residue (including fingerprints). Let dry
3. Wipe the inside of the "C" shaped Foam Strip with Solvent to remove any residue. Let dry


4. OPTION: Notch Curved Corner Section



- where you have a sharp corner, you may need to notch the edges of the Slim "C" Strip where they go around the corner to prevent buckling
- cutting these notches will help the strip lie down flatter around the curves

5. Apply Boing 400 adhesive to the inside of the Foam Strip

- **Do NOT put too much adhesive or it will not dry!!!!**
- Ensure the adhesive is also along outer edges.
- Start at one end of the strip near the middle of the cart.
- Apply adhesive to the first 6 inches - let it set (average 30 seconds).
- After "anchoring" the first part of the strip continue with adhesive 12" at a time
- lift up and put back the strip to help spread the adhesive
- press down and hold to ensure proper bond



6. Continue the same way with the second Foam Strip starting from the same spot, but going in the opposite direction



- For larger carts, there may be a small gap left over.
- Cut, and insert the "gap filler" strip into the space using Boing 4000 adhesive

8. Use "Duct Tape" as needed to temporarily hold the Foam Strips in place



9. After 5 minutes, carefully remove any duct tape

10. If you missed a spot you can go back and do touch-ups with the adhesive

Other Padding products available for different shaped carts

Quantity of these strips will depend on dimensions of cart

Follow the same "basic" installation instructions as above for the slim "C" strips



Slim V - 72"



Flat Pad - 39.4"



Basic Strip - 39.4"



3-D Jumbo Corner



2-D Jumbo Corner

SOLVENT: Mineral Spirits or Laquer Thinner or Acetone

CLEANING & MAINTENANCE:

Use any general household cleaner + soft cloth

Do not use harsh abrasive scrubbing agents

Do not use strong chemicals like Citrus spray or Bleach

Boing Safety

136 Walker Street, Atlanta GA 30313

TEL 404-521-9054 ORDER: 800-477-6434 FAX: 404-222-8366

wwwBoingSafety.com info@BoingSafety.com